

Leica CM1950 Platform

The Disinfecting Clinical Cryostats

Leica CM1950 Platform

The cryostats for high quality sectioning, user safety, and efficient workflow

The Leica CM1950 platform is the latest innovation in a long line of distinguished cryostats manufactured by Leica Biosystems. Leica designed and developed the new family of cryostats based upon users' feedback and their requirements for high quality sections, user safety, and efficient laboratory workflow.

HIGH QUALITY SECTIONING	USER SAFETY	EFFICIENT WORKFLOW	
 High precision microtome with stepper motor object feed Motorized sectioning (optional) Stable specimen clamp system Flat specimen discs for high specimen stability Rapid freezing shelf design Effective object cooling system (optional) 	 UVC disinfection AgProtect[™] antimicrobial nanosilver surface coating Disposable blade holder CE Debris-free, frost-free enclosed microtome assembly Leica's Section Waste Removal System (optional) Spacious cabinet with rounded edges inside and out 	 UVC disinfection at any time and temperature Organized work space inside and out Frost-free, encapsulated microtome assembly Leica's Section Waste Removal System with easily-accessible, concealed filter system (optional) Easily recognizable control symbols Visible operating parameters at 	



- 1 The brightly lit, ergonomic cryocabinet is spacious enough to allow efficient handling of multiple specimens.
- 2 Store tools, glass slides, staining containers, etc. in a recessed area on top of the cryostat to have these items immediately at hand.
- **3** For extra ease of use and consistent sectioning of all specimen types, an optional sectioning motor drive is available.
- 4 Learn quickly and work confidently using the externally located, selfexplanatory controls with easily recognizable symbols.
- 5 For an extra measure of safety, the inside of the instrument features an ozone-free UVC disinfection system that is certified to be effective against most bacteria, virus, and fungi, even at cold temperatures.
- 6 Increased safety for the user and others in the immediate work area: Leica's AgProtect[™] antimicrobial nanosilver surface coating deters the propagation of infectious agents on the outside of the instrument.
- 7 To protect the laboratory environment from contamination, a multi-filter system (including HEPA filter) removes particulates and cleans the air exhausted from the optional Section Waste Removal System.
- 8 Liquid condensate is safely collected in an easily accessible waste container.

High Quality Sectioning

Obtain high quality sections through:

- NEW: CryoZone[™] blade holder and anti-roll guide cooling
- Maintaining the ideal object temperature for specific specimens
- Great stability of the microtome and blade holder system
- Extreme accuracy of the stepper motor object feed
- Consistent motor-driven cutting stroke (optional)
- Vacuum-assisted sectioning aid (optional)
- High precision microtome with exact stepper motor object feed

COOL AIR CIRCULATION

EFFICIENCY

The cool way to improve section quality! The CryoZone™ system controls a zone of uniformly cool air in the critical areas of the cryochamber. This cool air circulates around the specimen, knife and anti-roll guide to create the optimal conditions for consistent, high-quality sectioning.



Efficient specimen loading is achieved via single lever operation that provides maximum clamping force independent of individual user strength. Direct contact cooling through the (optional) actively cooled object head facilitates rapid changes of specimen temperatures to provide the best conditions for sectioning various specimen types.

FAST FREEZING

High specimen stability is achieved by adherence to deeply grooved specimen discs. Specimens freeze quickly because the pre-cooled discs feature a large back surface that fully contacts the freezing shelf with integrated Peltier element.











VIBRATION-FREE SECTIONING

Superior sectioning of routine, hard, and/or large samples is achieved using a choice of knife/blade holders as well as the new dove tail mounting system that provides increased stability and extended working distance. The new CE holder for high and low profile disposable blades evenly distributes clamping pressure across the entire length of the blade, which provides vibration-free sectioning.

- 1. Knife holder CN for steel knives (optional accessory)
- 2. Knife holder CNZ for steel or tungsten carbide knives (optional accessory)
- 3. The optional vacuum sectioning aid achieves time-saving section preparation and reduces section curling



Highest User Safety

Histology laboratories continue to express major concerns about biohazard exposure and non-ergonomic work practices. As a result of their feedback, the Leica CM1950 family of cryostats is designed to provide maximum protection from these risks at all stages of the sectioning process.



- Certified UVC disinfection of exposed surfaces and air within the cryochamber at cold temperatures
- AgProtect[™] antimicrobial nanosilver coating on the outside surfaces of the cryostat to efficiently reduce the propagation of infectious agents. Silver (Ag) ions are well documented for their ability to reduce bacterial growth
- Optional Section Waste Removal System with a series of three filters
- Ergonomic exterior cabinet design with rounded edges and comfortable working height
- Optional ergonomic chair and foot rest

COMFORTABLE WORKING

The ergonomic design of the Leica CM1950 protects the user from sharp edges and helps prevent workrelated musculoskeletal disorders (MSD) and repetitive strain injury (RSI). Rounded edges allow the user to adopt a comfortable working position. Bright, glare-free illumination helps reduce eye fatigue.

DISPOSABLE BLADE HOLDER CE

The new disposable blade holder CE with integrated, colored safety guard and blade removal aid makes blade handling safer. For users who prefer using the brush technique during sectioning, the palm rest can be used instead of the anti-roll guide.

USER COMFORT

For individual user comfort, the Leica chair and height adjustable foot rest are available as optional accessories.













SECTION WASTE REMOVAL

Section waste is easily removed by using Leica's Section Waste Removal System during trimming with the magnetized nozzle (1), or during extensive cleaning with the flexible hose (2). Solid waste is collected in a concealed primary filter system and air is filtered through a HEPA filter for added safety in the laboratory environment. Liquid condensate is collected in a condensate bottle for safer disposal.

UVC DISINFECTION

Leica Biosystems', built-in UVC disinfection system provides certified protection from infectious material and minimizes the risk of contamination in the cryochamber. Scientific studies prove that surface disinfection from bacteria, viruses, and fungi can be achieved with UVC light. Certification proving the effectiveness of UVC disinfection against a range of microorganisms can be downloaded from www.LeicaBiosystems. com, which includes detailed information on the test procedure and the efficacy of UVC disinfection.

Highly Efficient Workflow

The best workflow for efficient operation is achieved by:

- Simple specimen identification using the optional, color-coded specimen discs
- Fast, efficient specimen orientation with clearly defined zero position
- Disposable blade holder for both high and low profile blades
- Frost-free, enclosed microtome assembly
- Optional motor drive for specimen sectioning
- Certified UVC disinfection at low temperatures does not produce condensation or contaminated waste, is effective at low temperatures, and can be terminated at any time to process urgent cases

FOR MULTIPLE USERS

SPECIMEN ORIENTATION

The self-explanatory, single-function keys and easily readable LEDs help prevent operating errors, facilitate cryosectioning, and make scrolling through multiple menus unnecessary. The control panels are comfortably positioned in the armrests to eliminate the need to reach into the cold chamber to use or adjust settings.



A clearly defined zero-position allows faster specimen alignment prior to sectioning and easy realignment if the specimen is removed from the object head.

DISPOSABLE BLADE HOLDER

With the disposable blade holder CE blade exchange is simple and fast. The holder's lateral displacement function allows the use of the full length of the blade. Small and large sections are easily lifted from the large, horizontal pressure plate.











3

- The specimen discs can be pre-cooled in the optional internal storage container, and then easily organized and transported.
- 2. Sectioning tools/aids etc. can be conveniently placed on the optional, movable shelf.
- Optional color coded specimen discs help identify specimens come from multiple sources. The specimen disc features a visual specimen orientation aid to enable precise orientation.

Leica CM1950 Technical Specifications

The Leica CM1950 basic instrument is equipped with CryoZone[™] technology, UVC Disinfection, specimen orientation and **Ag**Protect[™] antimicrobial nanosilver coating.

An individual, tailor-made instrument can be configured by use of the various options available:

- Actively cooled object head (double compressor)
- Vacuum Section Waste Removal System
- Motorized Sectioning
- A wide range of accessories

UVC surface disinfection:	30 or 180 minutes, user selec	nutes, user selectable	
Microtome			
Section thickness range:	Setting values:	1 to 100 μm	
		1.0 μm – 5.0 μm in 0.5 μm steps	
		5.0 μm – 20.0 μm in 1.0 μm steps	
		20.0 µm – 60.0 µm in 5.0 µm steps	
		60.0 μm – 100.0 μm in 10.0 μm steps	
Trimming range:	Clinical:	10 – 40 µm	
	Setting values:	10 μm, 20 μm, 30 μm, 40 μm	
	Research:	1 – 600 μm	
	Setting values:	1,0 μm — 10,0 μm in 1,0 μm steps	
		10,0 µm — 20,0 µm in 2,0 µm steps	
		20,0 µm – 50,0 µm in 5,0 µm steps	
		50,0 μm – 100,0 μm in 10,0 μm steps	
		100,0 μm — 600,0 μm in 50,0 μm steps	
Maximum specimen size:		50 x 80 mm	
Total specimen feed:		25 mm	
Vertical specimen stroke:		59 mm	
Specimen retraction:		20 µm or off	
Specimen orientation:		8° (x-, y-axis), 360° rotation of specimen disc	
Electric coarse feed:	Slow:	300 µm/s, in 20 µm steps	
	Fast:	900 µm/s	
Cryochamber			
Temperature range:		0 °C to -35 °C at ambient temperature of 20 °C	
Specimen Cooling (optional)	Temperature range:	-10 to -50 °C	
Defrosting of specimen head:		manual defrost	
Cryochamber defrosting			
Automatic cryochamber defrosting:		programmable, (hot gas defrost),	
		selectable time,	
		1 defrost in 24 h or manual hot gas defrost,	
		defrost time: 12 minutes	
Automatic shut off defrost:		at – 5 °C chamber temperature	

Quick-freeze shelf	
Minimum temperature:	down to – 42 °C, at chamber
	temp. – 35°C
Number of freezing stations:	15 + 2
Defrost:	manual hot-gas defrost
Peltier element	
Number of freezing stations:	2
Maximum temperature difference:	17 K, at chamber temp. of – 35 °C
Power draw	1900 VA
General information	
Operating temperature range:	18°C to 35°C
Relative humidity:	max. 60%, non-condensing
Storage humidity:	< 60%
Dimensions and Weights	
Width (without handwheel):	700 mm
Width (with handwheel):	835 mm
Depth (cabinet only):	800 mm
Height (total):	1215 mm
Working height (armrest):	1025 mm
\A/ * 1.	
Weight:	165 kg
Weight (with vacuum):	183 kg
Weight (with motor):	185 kg
Weight (with motor and vacuum):	193 kg

Choice of blade or knife holders:

Stable blade holder base with segment arc for lateral displacement of the blade. Disposable blade holder insert CE for high and low profile blades with 2 anti-roll guides with 50 and 100 µm spacer with glare minimizing glass insert, colored safety guard and blade removal help. Palm rest for brush technique.

Stable knife holder base for knife holder CN or knife holder CNZ. Knife holder CN for reusable steel knives Knife holder CNZ for reusable steel or tungsten carbide knives with central pressure plate for full usage of the knife.

Wide range of accessories available on request. Technical specifications subject to change without prior notice. As confirmed by the successful c_CSA_us certification, the Leica CM1950 has been designed and manufactured in compliance with US, Canadian and IEC requirements.

The Cryostats for high quality sectioning, user safety and efficient Lean Histology[™] workflow.







TOTAL CRYOSECTIONING SOLUTIONS

Leica ST4020 Linear Stainer

Quickly and easily stain surgical frozen sections with this small, fast stainer located near or on top of your cryostat.

Disposable Blades

Find just the blade you need from Leica Biosystems' diverse range of coated, uncoated, high- and low-profile blades.

Leica Surgipath Slides

With many color and adhesive options you're sure to find the ideal slide for your application.

Embedding Media

Leica Biosystems can supply a wide range of embedding media including Tissue Freezing Medium, FSC22™ and Cryo-Gel.

Dr. Peters Cryoembedding System

Easily achieve proper specimen orientation and perfect embedding with the unique Precision Cryoembedding System.

LEICA BIOSYSTEMS

Leica Biosystems is a global leader in workflow solutions bringing histopathology laboratories and researchers the highest quality, most comprehensive product range in anatomical pathology. With complete histology systems featuring innovative automation, Novocastra[™] reagents and Surgipath[®] consumables, Leica Biosystems offers the ideal product for each histology step and high-productivity workflow solutions for the entire laboratory.

Leica Biosystems – an international company with a strong network of worldwide customer services:

North America	800 248 0123
Asia/Pacific Sales and Customer Support	
Australia	1800 625 286
China	+85 2 2564 6699
Japan	+81 3 5421 2804
South Korea	+82 2 514 65 43
New Zealand	0800 400 589
Singapore	+6567797823

For detailed contact information about European sales offices or distributors please visit our website. Leica Biosystems brings together products, quality and support. Offering a complete solution that helps you advance workflows, enhance diagnostic clarity and deliver what really matters – better patient care.

